



Biometric technology at your fingertips.

No external databases, all personal data remains on the card. Only the owner can activate the card, which then sends standard signals to the host system.

Programmable contactless biometric communication 14443 desfire ev1 and mifare classic compatible.

- RELIABLE TECHNOLOGY Offering consistent fingerprint reads with every use.
- SECURE Unique to the user, only the owner can activate the card communication with the reader.
- DURABLE
 Strong and resistant to cracking and breaking.
- COMPATIBLE
 Works with nearly all existing 14443 readers.
- EFFICIENT Providing an easy, low cost biometric upgrade path for existing access control systems.
- PRIVACY Fingerprint data is stored on the card, not in any external database.
- PROGRAMMABLE Standard NFC 14443 technology programming procedures.



Features:

- On-card fingerprint scanner with 3D capacitive technology.
- Universal compatibility with all ISO 14443 readers.
- Secure template management, the fingerprint never leaves the card.
- Only the owner can operate Zwipe cards.
- Quickly reads in less than one second.
- Easy to program.





SPECIFICATIONS

Dimensions	8.518 cm × 5412 cm × 0.5 cm (L×W×H) 3.35354" × 2.13071" × 0.19685" (L×W×H)	
Weight	21 grams 0.740753oz	
Frequency	13.56MHz	
ISO standard	ISO 14443	
Construction	Plastic (casing), Cu (plating), FR4 (pre-impregnated resin fiberglass)	
Operating temperature	-20°C to 40°C -4°F to 104°F	
Baud rate (data transfer)	Up to 848 kbit/s -> up to 848 kBd	
Warranty	3 years	